

Lane closure trailer		ZPP - 3
<b>Chassis and equipment:</b>		
Type / weight / capacity:	AP 2700 / 2700 / 1920 kg	
Dimensions: (L x W x H)	5500 x 2200 x 2950 mm	
Wheels:	14 / 185 R14 x (4 + 1)	
Trailer hitch:	Ø 50 - globular / Ø 40 -thorn	
Brakes:	running - inertial / parking - mechanical	
Electrical installation; voltage; connection:	ECE R 48.1; 12 - 24 V with TLC 2412S; ISO 1724	
Battery; charger; cable-reel:	12 V / 143 Ah ; ADP 400; 10 m - 3 x 1,5 mm <sup>2</sup>	
Overall temperature range:	-30 .. +50 °C	
<b>Signaling panels:</b>		
LED arrow; width / leg; light intensity seg. / arrow; f. v. angle:	yellow; 210 / 1000 mm; > 2 / > 20 kcd (EN 12352 - L9H); 28°	
Voltage / consumption:	10 - 15 V DC / 3 A	
Flashing lights / consumption:	Ø 340 mm, with shade; 12 V DC / 1 A	
Reflecting foil:	type II - High intensity	
Dimensions (W x H x D):	2200 x 1700 x 2500 mm	