

Full graphic screen trailer		LE - 3D
Chassis and equipment:		
Type / weight / capacity:	AP 850 / 850 / 350 kg - basis chassis	
Dimensions (L x W x H):	2650 x 1920 x 3250 mm	
Wheels:	14 / 185 R14 C x (2 + 1)	
Trailer hitch:	Ø 50 - globular / Ø 40 - thorn	
Brakes:	running - inertial / parking - mechanical	
Electrical installation; voltage; connection:	ECE R 48.1; 12 - 24 V with TLC 2412S; ISO 1724	
Battery; charger; cable-reel:	12 V / 230 Ah ; ADP 400; 10 m - 3 x 1,5 mm ²	
Hydraulic pump; lifting consumption; elevation time:	12 V DC / 600 W; 7 A; < 30 s	
Overall temperature range:	-30 .. +50 °C	
Upper screen:		
LED; matrix; raster; brightness; f.v.angle:	red / yellow Ø 5 mm; 2 x 80 x 64; 17,5 mm; 9 kcd / m ² ; 30°	
Voltage / consumption / standby:	9 - 15 V DC / 3 - 5 A / 0,2 A	
Flashing lights / consumption:	Ø 340 mm, with shade; 12 V DC / 1 A	
Rotating lights:	12 V DC / 1,2 A	
Dimensions (W x H x D) / weight:	1800 x 1250 x 200 mm / approx. 110 kg	
Lower screen:		
LED; matrix; raster; brightness; f.v.angle:	yellow Ø 5 mm; 64 x 32; 25 mm; 4,8 kcd / m ² ; 30°	
Voltage / consumption / standby:	9 - 15 V DC / 2 - 4 A / 0,1 A	
Dimensions: (W x H x D) / weight	1800 x 1000 x 200 mm / approx. 500 kg	